

**The Pro's Choice for Powerful and
Safe Odor Elimination**

THE ODOROX HG

BOSS XL3



PATENTED • SCIENTIFICALLY CONFIRMED • SAFETY TESTED • FIELD PROVEN



» BOSS XL3

The Odorox® Boss XL3™ machine is ideal for disaster restoration contractors treating moderate to severe odors in medium to large areas. It is a versatile unit that can be used to eliminate a wide array of odors and VOCs. It works on difficult odors resulting from fires, floods, sewage backups, fuel spills, skunks, chemical spills, trauma scenes, nicotine, mold, etc.

This unit must be used with a centrifugal air mover (air mover is NOT included). It uses 3 ultraviolet optics and operates using 1.6 amps.

The typical coverage area for this machine is 1,000 to 1,500 sq. ft., depending upon the strength of the odor and the layout of the structure. The coverage area may be 2,000 to 2,500 sq. ft. for lighter odors and open floorplans.

SPECIFICATIONS

Dimensions	11.12" x 20.25" x 20.25" (282.4mm x 514.4mm x 514.5mm)
Weight	25lbs (11.4kg)
Power	120V @ 1.6 Amps
Control	Selector Switch & Pressure Switch which activates from positive air flow
Meter	1/10 quartz hour meter
Mobility	Handle / Rubber feet
Finish	Black powder coat
Noise Level	N/A
Number of Optics	3
Air inlet / Outlet	Louvered panel/7" (117.8mm) Spout
Fans & Rating	N/A
Filter	One 9.75" x 10.68" x 0.50" (247.7mm x 271.3mm x 12.7mm)
Certification	ETL Canada/US - CSA & UL Standards Meet or Exceed EPA - OSHA Standard & Guidelines Residual O3/Non-accumulative

**The State of California requires the following label:
"Solely for industrial use. Potential health hazard: emits ozone."**